

S/N 09/575348

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant:

09/575348

Examiner:

Serial No.:

09/575348

Group Art Unit:

Filed:

May 19, 2000

Docket No.:

-NT ENED
NT EIVED
NT I 2003
1742
12052.33US01GROUP 1700
PACTURING
TUOUSLY

Title:

BILLET FOR COLD FORGING, METHOD OF MANUFACTURING

BILLET FOR COLD FORGING, METHOD OF CONTINUOUSLY COLD-

FORGING BILLET, METHOD OF COLD-FORGING

CERTIFICATE UNDER 37 CFR 1.6(d):

I hereby certify that this paper is being transmitted by facsimile to the U

VOLUNTARY AMENDMENT

Mail Stop Non-Fee Amendment P.O. Box 1450 Alexandria, VA 22313-1450

Dear Sir:

Please amend this application as follows:

IN THE CLAIMS

- 1. (FIFTH AMENDED) A billet of steel for continuous cold forging, consisting essentially of 0.46 - 0.48 wt % of C (carbon), 0.14 wt % or less of Si (silicon), 0.55 - 0.65 wt % of Mn (manganese), 0.015 wt % or less of P (phosphorus), 0.015 wt % or less of S (sulfur), 0.15 wt % or less of Cu (copper), 0.20 wt % or less of Ni (nickel), and 0.35 wt % or less of Cr (chromium), wherein a carbide of the billet is spheroidized and the billet has a limiting upsetting ratio of 90 % or more without the occurrence of cracks.
- 2. (FIFTH AMENDED) A billet of steel for continuous cold forging, consisting essentially of 0.46 - 0.48 wt % of C (carbon), 0.14 wt % or less of Si (silicon), 0.55 - 0.65 wt % of Mn (manganese), 0.015 wt % or less of P (phosphorus), 0.015 wt % or less of S (sulfur), 0.15 wt % or less of Cu (copper), 0.20 wt % or less of Ni (nickel), and 0.35 wt % or less of Cr (chromium), wherein a carbide of the billet is spheroidized and has an aspect ratio of 300 % or